

# Blauberg Horizontal Komfort Ultra D105-A



**Komfort Ultra D105-A is suitable for extracting from 2 locations and supplying to two locations with controllable air exchange for creating the best heat comfort in your home**

**This unit is controlled by an external speed switch to control the units three fan speeds**

Model	Blauberg Komfort Ultra D105-A
Heat Recovery efficiency %	Up to 72%
Airflow Rate Max m3/h	106
Airflow Rate @ -PA m3/h	90 @ 50Pa
Max dwelling size m2 @ .3 ACH	60
Max dwelling size m2 @ .5 ACH	55
Max room extraction	Kitchen + 1 wet rooms
ERP Rating	D
Specific fan power (lowest)	Pending
Dimensions W x H x D (mm)	374x224x497
Weight	13Kg
Filtration	2 x G4
Pre/ Post Heater	Accessory
Summer Bypass	No
Frost protection	Freeze protection system
Sound level @3m db.(a)	24
Mounting	Floor / Ceiling
Ductwork connections	4 side ductwork connections
Duct Diameter	125mm
Condensate Drain	Condensate drainage kit available separately
Warranty	1 year
Country of manufacture	Germany
Heat exchanger	PVC
Digital Controller	3 speed
Boost Switch control	No (optional timer box)
Interactive App Control	No
Internal Humidity Control	No
Available room sensors	n/a
BMS	n/a
KNX	n/a
SAP Appendix Q	Pending
Fireplace mode	n/a
Alarm system integration	n/a
Passive House	No